



TX-5300E



TX-5300

Your Versatile Partner

TX-5300/TX-5300E

Powerful Fanless POS Box

TX-5300 Series is the latest high-end fan-free POS Boxes. Incorporating leading CPU Technology – 8th generation Intel® Coffee Lake processor, TX-5300 series provide unmatched performance while juggling multiple program with ease.

TX-5300/TX-5300E

High Performance

With SSD and 8th generation Intel Coffee Lake, TX-5300 series (Core i3 processor) are faster, cooler and more efficient. In conjunction with patented fan-free technology, they deliver the unparalleled performance at completely silent operation.

Compact and Hassle-free

Small footprint design allow TX-5300 series to be placed anywhere you need a Point of Service System. Built-in PoweredUSB ports free up the need for multiple power adapters for peripherals and keep the counter neat and tidy.

Expandable and Flexible

Connect to a wide range of POS peripherals and options for greater productivity and flexibility to fit in your store environment.

Specification	TX-5300	TX-5300E
Processor	Intel Coffee Lake Core i3-8100T (default)	
System Memory	DDR4 SO-DIMM X2, max. 32GB	
Storage Device	SATA III x 2 + M.2 x 1 (supporting SATA)	
RAID	N/A	
vPro	N/A	
TPM	N/A	
Power Supply	12V/80W	12V/150W
OS Support	Window 10 IoT 64 bit/Linux per request	

I/O & Expansion

Serial Port	6, DB9 x 4, COM5/COM6 via optional cable from service window, 5V/12V support on all COM ports	
Parallel Port	1	
Standard USB Port	7, USB 3.0 x 4 + USB 2.0 x 3	4, USB 3.0 x 4
PoweredUSB Port	N/A	3, 24V x 1 + 12V x 2
LAN Port	10/100/1000 Mb x 2	
Display Port	VGA x 1, 12V support for Posiflex monitors; HDMI x 1	
CR Port	1, control 2 CR via optional Y-cable, support 24V	
PS/2 Port	N/A	
USB Port	N/A	
Audio	2W internal speaker x 1 + Mic-in/Line-out	
Expansion Slot	M.2 slot x 1	

Built-in Option

WiFi	M.2 WiFi/BT module
------	--------------------

Physical Dimension

Dimension (W x D x H in mm)	220 x 202 x 83
Weight (N. W. in kg)	2.75

Environmental

Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

Certifications	      	EN20 1008V3
----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------

POSIFLEX

LSI Software S.A. Generalny dystrybutor Posiflex w Polsce
 tel.: 22 865 77 44 | tel.: 22 610 77 42 | fax.: 22 379 17 28
 e-mail: info@posiflex.com.pl | www.posiflex.com.pl

Autoryzowany Dystrybutor / Sprzedawca: